Smarter, Better, Stronger!











Highlights

Extreme workload range of 10 - 3000 watt

This extraordinary peak workload is extremely suitable for sports medicine and testing the strongest athletes on their anaerobic power or isokinetic capacity. Combined with the low start workload of 10 Watt this Excalibur will fit everybody.

Suitable for all types of athletes

The ergometer can be used for various tests, like e.g. Wingate, Isokinetic, HIT and timetrials. Moreover CPET testing and bike fitting is possible, allowing all types of athletes to be tested.

Extreme adjustability

Both the saddle and the handlebar can be adjusted horizontally and vertically using the control unit.

Exchangeable accessories

The pedals, handlebar and saddle can easily be exchanged for the Test Subjects own accessories to test the Test Subject as realistic as possible, to optimize the circumstances or exchange to test a better bike fitting.

Heavy Duty Design

The Excalibur Sport is designed for heavy duty sports medicine ergometry, without doing any concession on the esthetic, modern and robust design. In other words: Excalibur Sport: the gold standard in Ergometry!





Smarter, Better, Stronger!



With its unbeatable accuracy and reliability, the Excalibur Sport has proven itself as The Gold Standard in Ergometry ever since 1985. However, the world keeps spinning and developments never stop. That is why we now proudly present the new Lode Excalibur Sport: Smarter, Better and Stronger! Still true to its heritage but combined with innovative new features to meet the latest and future requirements of modern sports medicine and research to allow athletes to become stronger and better with smarter use of human performance technology.

Versatile ergometer

The new Lode Excalibur Sport ergometer is an essential part of a sports medicine or research lab, since it can be used to test all types of athletes. The ergometer allows for various tests, like a Wingate sprint test, lsokinetic tests, High Intensity Tests (HIT) and time trials. Moreover, it can also be used for CPET testing and bike fitting.

This ergometer is standard supplied with a 7" control unit and a USB A-B cable to connect to cpet devices.





Smarter, Better, Stronger!

Features



Electric adjustable saddle Excalibur Sport

The position of the saddle of the excalibur sport can be adjusted in height, length and angle to suit all users.

The saddle of the ergometer can be adjusted horizontally in a range of 252 mm and the saddle height in a range of 388 mm using the Control Unit or LEM.

The Test Subject can be seated on the saddle while adjusting.

Electric adjustable handlebar Excalibur Sport

The position of the handlebar of Excalibur Sport is completely adjustable in height and length.

The handlebar of the ergometer can be adjusted horizontally in a range of 169mm and vertically in a range of 390mm using the Control Unit or LEM software. The Test Subject can use the handlebar while adjusting.

10 watt

Extreme low start up load 10W

The extreme low start-up load of 10 watts and the adjustability in small steps of 1 watt make this ergometer perfectly suitable for many different applications. The standard control unit shows multiple ergometry parameters and you can determine your specific default setting and start-up menu.



Low noise

Due to accurate manufacturing and the careful choice of materials the product has an extremely low noise level.



Accurate over a long period of time

The Lode ergometers are supplied with an electro-magnetic braking mechanism of Lanooy (eddy current). The biggest advantage of this braking system compared to a friction braking system is the absolute accuracy and the accuracy over time. Moreover, friction braking systems have more wearing parts.



Compatible with ECG and pulmonary devices

The Lode ergometers have digital interfaces and can be controlled easily by all known stress ECG and pulmonary devices available in the world. This is one of the reasons why the Lode ergometers are very popular worldwide.



Exchangeable pedals

The cranks of the ergometer are suitable for almost all available clip systems so cyclists can perform a test with their own favorite pedals.



Designed to be sweat-proof

The housing of the ergometer is designed in such way that sweat does not have the chance to drip into the mechanical parts and cables are protected. This ensures a long lifetime and makes the ergometer insensitive for malfunction.

RS232 connectivity

RS232 ports enable connectivity to most ECG and ergospirometry devices as well as PC's.



LEM compatible

This product can be used with Lode Ergometry Manager (LEM) software to manage data and to apply specific protocols when a Communication card or Network card is present



Smarter, Better, Stronger!





Smarter, Better, Stronger!

SMARTER - The future is now

Adjustment of both the seat and the handlebar is possible in both a horizontal and vertical range. This adjustability can be controlled electrically through the display of the bike or LEM software, enabling easy optimization of the seating position. Moreover, the seat, handlebar and pedals can be exchanged easily for total adaption to the body posture and bike-fitting of each individual athlete.

You can extend the new Lode Excalibur Sport with the Lode Ergometry Manager Software, for faster availability of data and to simplify tha analysis of the tests. The latest Lode electrics makes the ergometer ready for the future.

BETTER - It's all about the details

The adjustability range of the New Excalibur Sport has improved considerably, making it possible for even more athletes to use the bike. The new touchscreen offers an easy user interface. You can determine yourself what data is made visible.

Furthermore, blood pressure measurement and SpO2 are available.

STRONGER - No sweat, no glory

The new Lode Excalibur Sport offers the highest performance testing with an unimaginable maximum peak load of 3000 watt! This load is fully supported by the new indestructible and sweat proof design. The bike is extrenely stable and cables are protected against sweat.





Smarter, Better, Stronger!

The new Excalibur Sport can a.o be extended with the following options:

USB to Serial converter Easy connection	Adjustable sports cranks incl. pediatric range Optimal force application	SpO2 for control unit with touch panel (extra long cable) Oxygen saturation	0-Watt start-up system Lowest possible startup power	Colour Display 3.5" - 2nd screen Multifunctionality
	R	And the second s	500 Zero Wall Option Actual Spin With Spin Sing my Spin Spin Sing my Spin	
Partnumber: 226012	Partnumber: 925808	Partnumber: 945822	Partnumber: 960805	Partnumber: 945819
RS232 cable Easy connection	Network module connection cable Easy connection	Add program function to 7" touch screen for ergometer Easily programmable	Blood Pressure with ECG trigger for bicycle ergometer with ECG trigger	Saddle for children Versatile ergometry
Partnumber: 930911	Partnumber: 930930	Partnumber: U945835	Partnumber: 945828	Partnumber: 401066
Saddle for children - ordered additionally	Bluetooth Smart heart rate	Suunto Belt HR Smart Bluetooth	Packaging upgrade to wooden box	Ambient sensor pack
Versatile ergometry	Heartrate available within an extreme wide	Smart connection	Ultra heavy duty packaging	Check environmental conditions during test
		auto	bicture not yet available	And the second s
Partnumber: P401066	Partnumber: 945833	Partnumber: 928639	Partnumber: U501155W	



Smarter, Better, Stronger!



70 cm

100 cm

145 kg

27.6 inch

39.4 inch

319.7 lbs

Specifications

Workload			User Interface		
Minimum load	10 W		English user interface	\checkmark	
Maximum peak load	3000 W		Norwegian user interface	\checkmark	
Isokinetic workload control	~		Czech user interface	\checkmark	
Minimum load increments	1 W		Danish user interface	\checkmark	
Hyperbolic workload control	~		Dutch user interface	\checkmark	
Linear workload control	\checkmark		French user interface	~	
Fixed torque workload control	\checkmark		German user interface	\checkmark	
Maximum rpm independent constant load 180 rpm			Italian user interface	\checkmark	
Minimum rpm independent constant load 30 rpm			Japanese user interface	\checkmark	
Electromagnetic "eddy current" braking system	\checkmark		Korean user interface	\checkmark	
Accuracy			Polish user interface	\checkmark	
Workload accuracy below 100 W	2 W		Portugese user interface	\checkmark	
Workload accuracy from 100 to 1500 W	2 %		Russian user interface	\checkmark	
Workload accuracy over 1500 W	5 %		Spanish user interface	\checkmark	
Comfort			Turkish user interface	\checkmark	
Toeclips on pedals	\checkmark		Ukrainian user interface	\checkmark	
Q-factor	147 mm		Terminal operation mode	\checkmark	
Vertical seat adjustment maximum	938 mm	36.9 inch	Screen size (diagonal)	17.8 cm	7 inch
Vertical seat adjustment minimum	550 mm	21.7 inch	Touchscreen	\checkmark	
Horizontal seat adjustment minimum	72 mm	2.8 inch	Connectivity		
Horizontal seat adjustment maximum	324 mm	12.8 inch	Control Unit with touch screen 7" for ergometer	\checkmark	
Allowed user weight	225 kg	496 lbs	Lode interface protocol	\checkmark	
Horizontal handlebar adjustment minimum	229 mm	9 inch	Ergoline P10 interface protocol	\checkmark	
Horizontal handlebar adjustment maximum	60 mm	2.4 inch	Ergoline P4 interface protocol	\checkmark	
Vertical handlebar adjustment minimum	465 mm	18.3 inch	Schiller interface protocol	~	
Vertical handlebar adjustment maximum	855 mm	33.7 inch	Bosch EKG 506 DS interface protocol	\checkmark	
			USB connector	~	
			RS232 out connector	~	
			Dimensions		
			Product length (cm)	200 cm	78.7 inch

Product width (cm)

Product height

Product weight

Power requi	rements
-------------	---------

VAC	100 - 240 V	
Phases	1	
Frequency	50/60 Hz	
Power consumption	160 W	
Power cord length	250 cm	98.4 inch
Power cord IEC 60320 C13 with CEE 7/7 plug	~	
Standards & Safety		
IEC 60601-1:2012 - pending	~	
ISO 13485:2016 compliant	~	
ISO 9001:2015 compliant	~	





Smarter, Better, Stronger!

Order info

Partnumber:

965910

*Specifications are subject to change without notice.



Distributed by **COMPEK MEDICAL SERVICES, s.r.o.** Dlouhá 615 50601 Jičín Czech Republic Tel: +420 493 524 534 Lode B.V. Zernikepark 16 9747 AN Groningen The Netherlands Tel: +31 50 5712811 Fax: +31 50 5716746 E-mail: ask@lode.nl Internet: www.lode.nl